



		最大静電容量(pF)-Y5P温度係数							NY2 シリーズ			
最大径 (mm)		500V <sub>DC</sub>	1KV <sub>DC</sub>	2KV <sub>DC</sub>	3KV <sub>DC</sub>	4KV <sub>DC</sub>	5KV <sub>DC</sub>	6KV <sub>DC</sub>	8KV <sub>DC</sub>	10KV <sub>DC</sub>	12KV <sub>DC</sub>	15KV <sub>DC</sub>
厚さ(最大値) (mm) ▶	4.0	5.0	6.0	6.0	7.0	7.0	8.0	9.0	10.0	10.0	12.0	
6	1000	680	470	330	300	270						
7	1500	1000	680	560	470	330	270					
8	2200	1500	1000	820	680	470	330	240	220			
9	3300	2200	1500	1000	1000	680	470	330	270	220	180	
10	3900	2700	1800	1500	1200	1000	680	470	330	300	270	
12	4700	3900	2200	1800	1800	1500	1000	680	680	470	390	
14	6800	4700	3300	2200	2200	1800	1500	1000	820	680	470	
16	10000	6800	4700	3300	2700	2200	2000	1500	1000	820	680	
18		10000	6800	4700	3300	3000	2700	2200	1500	1200	1000	
20			10000	6800	4700	3900	3300	2700	2000	1500	1200	

		最大静電容量(pF)-Y5U温度係数							NY2 シリーズ			
最大径 (mm)		500V <sub>DC</sub>	1KV <sub>DC</sub>	2KV <sub>DC</sub>	3KV <sub>DC</sub>	4KV <sub>DC</sub>	5KV <sub>DC</sub>	6KV <sub>DC</sub>	8KV <sub>DC</sub>	10KV <sub>DC</sub>	12KV <sub>DC</sub>	15KV <sub>DC</sub>
厚さ(最大値) (mm) ▶	4.0	5.0	6.0	6.0	7.0	7.0	8.0	9.0	10.0	10.0	12.0	
6	2200	1500	1000									
7	3300	2200	1500	1000	820	680	470					
8	4700	3300	2200	1500	1200	1000	680	470	390			
9	6800	4700	3300	2200	1800	1200	1000	680	470	430		
10	10000	6800	3900	2700	2200	1500	1200	1000	680	560	470	
12	15000	8200	4700	3300	2700	2200	1800	1500	1000	820	680	
14	22000	10000	6800	4700	3300	3300	2700	2200	1500	1200	1000	
16	27000	15000	10000	6800	4700	3900	3300	2700	2200	1800	1500	
18	33000	22000	15000	10000	6800	4700	3900	3300	2700	2200	1800	
20	39000	30000	22000	15000	10000	6800	4700	3900	3300	2700	2200	

		最大静電容量(pF)-Y5V温度係数							NY2 シリーズ			
最大径 (mm)		500V <sub>DC</sub>	1KV <sub>DC</sub>	2KV <sub>DC</sub>	3KV <sub>DC</sub>	4KV <sub>DC</sub>	5KV <sub>DC</sub>	6KV <sub>DC</sub>	8KV <sub>DC</sub>	10KV <sub>DC</sub>	12KV <sub>DC</sub>	15KV <sub>DC</sub>
厚さ(最大値) (mm) ▶	4.0	5.0	6.0	6.0	7.0	7.0	8.0	9.0	10.0	10.0	12.0	
6	3300	2200	1500	1000	820							
7	4700	3300	2200	2200	1500	1200	1000					
8	8200	4700	3300	3300	2200	1500	1200	1000				
9	10000	6800	4700	3900	3300	2200	1800	1200	1000			
10	15000	8200	6800	4700	3900	3300	2200	1800	1500	1000		
12	22000	10000	8200	6800	4700	3900	3300	3000	2200	1500	1000	
14	33000	15000	10000	8200	6800	5600	4700	3900	3300	2200	1500	
16	47000	22000	15000	10000	8200	7500	6800	4700	3900	3300	2200	
18	68000	33000	22000	15000	12000	10000	8200	6800	4700	4300	3600	
20	100000	47000	33000	22000	15000	12000	10000	8200	6800	5600	4700	

		最大静電容量(pF)-Z5P温度係数							NY2 シリーズ			
最大径 (mm)		500V <sub>DC</sub>	1KV <sub>DC</sub>	2KV <sub>DC</sub>	3KV <sub>DC</sub>	4KV <sub>DC</sub>	5KV <sub>DC</sub>	6KV <sub>DC</sub>	8KV <sub>DC</sub>	10KV <sub>DC</sub>	12KV <sub>DC</sub>	15KV <sub>DC</sub>
厚さ(最大値) (mm) ▶	4.0	5.0	5.0	6.0	6.0	7.0	7.0	8.0	9.0	10.0	12.0	
6	750	560	390	220	180	150	120					
8	1800	1200	820	470	390	330	300					
10	2700	2000	1200	820	680	560	470	390	330	240		
12	4700	3000	2000	1200	1000	820	750	620	470	360	300	
14	6800	4700	2700	1800	1500	1200	1000	820	750	560	430	
16	8200	6200	3900	2400	2000	1800	1500	1000	910	750	560	
18	10000	8200	4700	3300	2700	2200	1800	1500	1200	910	820	
20		10000	6800	3900	3600	3000	2400	2000	1500	1200	1000	

		最大静電容量(pF)-Z5U温度係数							NY2 シリーズ			
最大径 (mm)		500V <sub>DC</sub>	1KV <sub>DC</sub>	2KV <sub>DC</sub>	3KV <sub>DC</sub>	4KV <sub>DC</sub>	5KV <sub>DC</sub>	6KV <sub>DC</sub>	8KV <sub>DC</sub>	10KV <sub>DC</sub>	12KV <sub>DC</sub>	15KV <sub>DC</sub>
厚さ(最大値) (mm) ▶	4.0	5.0	5.0	6.0	6.0	7.0	7.0	8.0	9.0	10.0	12.0	
6	1800	1200	750	470	390	330	270					
8	3900	2400	1500	910	750	680	560					
10	6800	3900	2400	1500	1200	910	910	750	620	470		
12	10000	5600	3600	2200	1800	1500	1200	1000	910	750	560	
14	15000	8200	5600	3300	2700	2200	1800	1500	1200	1000	820	
16		10000	7500	4700	3600	3000	2400	2200	1800	1500	1000	
18			10000	6200	4700	3900	3300	3000	2400	1800	1500	
20				7500	6200	4700	4300	3900	3300	2400	2000	

- 1) 500V, 1KV, 2KV
- 2) 3KV/4KV
- 3) 5KV/6KV/8KV
- 4) 10KV/12KV

端子間 5mm	直径 10mm以上, 端子間隔 = 7.5mm or 10mm
端子間 7.5mm	直径 10mm以上, 端子間隔 = 10mm
端子間 10mm	直径 15mm以上, 端子間隔 = 12.5mm
端子間 10mm	直径 15mm以上, 端子間隔 = 12.5mm