



リード型金属酸化物バリスタ - 線間電圧シリーズ

SUPPRESSION

| CKE Part Number | Marking On Part | 最大許容回路電圧 | | バリスタ電圧 @ 1 mA DC | エネルギー耐量 2ms | 最大制限電圧 8/20 μs | | サージ電流耐量 | 静電容量 (標準値) | 外径寸法 (mm) - 図 64 | | | |
|-----------------|-----------------|-------------------|------|------------------|-------------|----------------|------|---------|------------|------------------|-----------------|-------|------|
| | | AC _{RMS} | DC | DC Volts | Joules | Volts | Amps | Amps | pF | D-Max | ± 1 mm T W d | | |
| Ⓜ Z130LA2 | 1302 | 130 | 170 | 200(185-225) | 11 | 340 | 10 | 1200 | 250 | 9.00 | 4.20 | 5.00 | 0.60 |
| Ⓜ Z130LA5 | 1305 | 130 | 170 | 200(185-225) | 20 | 340 | 25 | 2500 | 500 | 13.50 | 4.60 | 7.50 | 0.80 |
| Ⓜ Z130LA10A | Z130LA10A | 130 | 170 | 200(185-225) | 38 | 340 | 50 | 4500 | 1000 | 17.00 | 4.60 | 7.50 | 0.80 |
| Ⓜ Z130LA20A | Z130LA20A | 130 | 170 | 200(185-225) | 70 | 340 | 100 | 6500 | 2000 | 23.00 | 5.00 | 10.00 | 1.00 |
| Ⓜ Z140LA2 | 1402 | 140 | 180 | 220(198-242) | 12 | 360 | 10 | 1200 | 250 | 9.00 | 4.30 | 5.00 | 0.60 |
| Ⓜ Z140LA5 | 1405 | 140 | 180 | 220(198-242) | 23 | 360 | 25 | 2500 | 450 | 13.50 | 4.70 | 7.50 | 0.80 |
| Ⓜ Z140LA10A | Z140LA10A | 140 | 180 | 220(198-242) | 42 | 360 | 50 | 4500 | 1000 | 17.00 | 4.70 | 7.50 | 0.80 |
| Ⓜ Z140LA20A | Z140LA20A | 140 | 180 | 220(198-242) | 75 | 360 | 100 | 6500 | 2000 | 23.00 | 5.20 | 10.00 | 1.00 |
| Ⓜ Z150LA2 | 1502 | 150 | 200 | 240(216-264) | 13 | 395 | 10 | 1200 | 200 | 9.00 | 4.40 | 5.00 | 0.60 |
| Ⓜ Z150LA5 | 1505 | 150 | 200 | 240(216-264) | 25 | 395 | 25 | 2500 | 400 | 13.50 | 4.80 | 7.50 | 0.80 |
| Ⓜ Z150LA10A | Z150LA10A | 150 | 200 | 240(216-264) | 45 | 395 | 50 | 4500 | 900 | 17.00 | 4.80 | 7.50 | 0.80 |
| Ⓜ Z150LA20A | Z150LA20A | 150 | 200 | 240(216-264) | 80 | 395 | 100 | 6500 | 1800 | 23.00 | 5.30 | 10.00 | 1.00 |
| Ⓜ Z175LA2 | 1752 | 175 | 225 | 270(247-303) | 15 | 455 | 10 | 1200 | 170 | 9.00 | 4.60 | 5.00 | 0.60 |
| Ⓜ Z175LA5 | 1755 | 175 | 225 | 270(247-303) | 30 | 455 | 25 | 2500 | 350 | 13.50 | 5.00 | 7.50 | 0.80 |
| Ⓜ Z175LA10A | Z175LA10A | 175 | 225 | 270(247-303) | 55 | 455 | 50 | 4500 | 750 | 17.00 | 5.10 | 7.50 | 0.80 |
| Ⓜ Z175LA20A | Z175LA20A | 175 | 225 | 270(247-303) | 90 | 455 | 100 | 6500 | 1600 | 23.00 | 5.40 | 10.00 | 1.00 |
| Ⓜ Z210LA4 | 2104 | 210 | 275 | 330(297-363) | 15 | 550 | 10 | 1200 | 140 | 9.00 | 4.80 | 5.00 | 0.60 |
| Ⓜ Z210LA10 | 210L | 210 | 275 | 330(297-363) | 32 | 550 | 25 | 2500 | 300 | 13.50 | 5.20 | 7.50 | 0.80 |
| Ⓜ Z210LA20A | Z210LA20A | 210 | 275 | 330(297-363) | 60 | 550 | 50 | 4500 | 650 | 17.00 | 5.30 | 7.50 | 0.80 |
| Ⓜ Z210LA40A | Z210LA40A | 210 | 275 | 330(297-363) | 105 | 550 | 100 | 6500 | 1400 | 23.00 | 5.50 | 10.00 | 1.00 |
| Ⓜ Z230LA4 | 2304 | 230 | 300 | 360(324-396) | 15 | 595 | 10 | 1200 | 130 | 9.00 | 5.20 | 5.00 | 0.60 |
| Ⓜ Z230LA10 | 230L | 230 | 300 | 360(324-396) | 35 | 595 | 25 | 2500 | 300 | 14.00 | 5.70 | 7.50 | 0.80 |
| Ⓜ Z230LA20A | Z230LA20A | 230 | 300 | 360(324-396) | 65 | 595 | 50 | 4500 | 550 | 17.50 | 5.70 | 7.50 | 0.80 |
| Ⓜ Z230LA40A | Z230LA40A | 230 | 300 | 360(324-396) | 120 | 595 | 100 | 6500 | 1200 | 24.00 | 6.10 | 10.00 | 1.00 |
| Ⓜ Z250LA4 | 2504 | 250 | 330 | 390(351-429) | 21 | 650 | 10 | 1200 | 130 | 9.00 | 5.40 | 5.00 | 0.60 |
| Ⓜ Z250LA10 | 250L | 250 | 330 | 390(351-429) | 40 | 650 | 25 | 2500 | 270 | 14.00 | 5.80 | 7.50 | 0.80 |
| Ⓜ Z250LA20A | Z250LA20A | 250 | 330 | 390(351-429) | 72 | 650 | 50 | 4500 | 500 | 17.50 | 5.80 | 7.50 | 0.80 |
| Ⓜ Z250LA40A | Z250LA40A | 250 | 330 | 390(351-429) | 130 | 650 | 100 | 6500 | 1000 | 24.00 | 6.40 | 10.00 | 1.00 |
| Ⓜ Z275LA4 | 2754 | 275 | 350 | 430(387-473) | 23 | 710 | 10 | 1200 | 110 | 9.00 | 5.70 | 5.00 | 0.60 |
| Ⓜ Z275LA10 | 275L | 275 | 350 | 430(387-473) | 45 | 710 | 25 | 2500 | 250 | 14.00 | 6.20 | 7.50 | 0.80 |
| Ⓜ Z275LA20A | Z275LA20A | 275 | 350 | 430(387-473) | 75 | 710 | 50 | 4500 | 450 | 17.50 | 6.20 | 7.50 | 0.80 |
| Ⓜ Z275LA40A | Z275LA40A | 275 | 350 | 430(387-473) | 140 | 710 | 100 | 6500 | 900 | 24.00 | 6.70 | 10.00 | 1.00 |
| Ⓜ Z300LA4 | 3004 | 300 | 385 | 470(423-517) | 25 | 775 | 10 | 1200 | 100 | 9.00 | 6.00 | 5.00 | 0.60 |
| Ⓜ Z300LA10 | 300L | 300 | 385 | 470(423-517) | 45 | 775 | 25 | 2500 | 230 | 14.00 | 6.20 | 7.50 | 0.80 |
| Ⓜ Z300LA20A | Z300LA20A | 300 | 385 | 470(423-517) | 80 | 775 | 50 | 4500 | 440 | 17.50 | 6.20 | 7.50 | 0.80 |
| Ⓜ Z300LA40A | Z300LA40A | 300 | 385 | 470(423-517) | 150 | 775 | 100 | 6500 | 900 | 24.00 | 6.70 | 10.00 | 1.00 |
| Ⓜ Z350LA10 | 350L | 350 | 455 | 560(504-616) | 45 | 925 | 25 | 2500 | 180 | 14.00 | 6.10 | 7.50 | 0.80 |
| Ⓜ Z350LA20A | Z350LA20A | 350 | 455 | 560(504-616) | 80 | 925 | 50 | 4500 | 350 | 17.50 | 6.30 | 7.50 | 0.80 |
| Ⓜ Z350LA40A | Z350LA40A | 350 | 455 | 560(504-616) | 150 | 925 | 100 | 6500 | 700 | 24.00 | 6.80 | 10.00 | 1.00 |
| Ⓜ Z385LA10 | 385L | 385 | 505 | 620(558-682) | 45 | 1025 | 25 | 2500 | 130 | 14.00 | 6.20 | 7.50 | 0.80 |
| Ⓜ Z385LA20A | Z385LA20A | 385 | 505 | 620(558-682) | 85 | 1025 | 50 | 4500 | 250 | 17.50 | 6.50 | 7.50 | 0.80 |
| Ⓜ Z385LA40A | Z385LA40A | 385 | 505 | 620(558-682) | 150 | 1025 | 100 | 6500 | 500 | 24.00 | 6.90 | 10.00 | 1.00 |
| Ⓜ Z420LA10 | 420L | 420 | 560 | 680(612-748) | 45 | 1120 | 25 | 2500 | 130 | 14.00 | 6.50 | 7.50 | 0.80 |
| Ⓜ Z420LA20A | Z420LA20A | 420 | 560 | 680(612-748) | 90 | 1120 | 50 | 4500 | 250 | 17.50 | 6.50 | 7.50 | 0.80 |
| Ⓜ Z420LA40A | Z420LA40A | 420 | 560 | 680(612-748) | 160 | 1120 | 100 | 6500 | 460 | 24.00 | 6.90 | 10.00 | 1.00 |
| Ⓜ Z460LA10 | 460L | 460 | 615 | 750(675-825) | 50 | 1240 | 25 | 2500 | 120 | 14.00 | 6.80 | 7.50 | 0.80 |
| Ⓜ Z460LA20A | Z460LA20A | 460 | 615 | 750(675-825) | 100 | 1240 | 50 | 4500 | 230 | 17.50 | 6.80 | 7.50 | 0.80 |
| Ⓜ Z460LA40A | Z460LA40A | 460 | 615 | 750(675-825) | 175 | 1240 | 100 | 6500 | 420 | 24.00 | 7.30 | 10.00 | 1.00 |
| Ⓜ Z480LA20 | 480L | 480 | 640 | 780(702-858) | 50 | 1290 | 25 | 2500 | 120 | 14.00 | 6.90 | 7.50 | 0.80 |
| Ⓜ Z480LA40A | Z480LA40A | 480 | 640 | 780(702-858) | 105 | 1290 | 50 | 4500 | 230 | 17.50 | 6.90 | 7.50 | 0.80 |
| Ⓜ Z480LA80A | Z480LA80A | 480 | 640 | 780(702-858) | 180 | 1290 | 100 | 6500 | 420 | 24.00 | 7.40 | 10.00 | 1.00 |
| Ⓜ Z510LA20 | 510L | 510 | 670 | 820(738-902) | 55 | 1355 | 25 | 2500 | 105 | 14.00 | 7.10 | 7.50 | 0.80 |
| Ⓜ Z510LA40A | Z510LA40A | 510 | 670 | 820(738-902) | 110 | 1355 | 50 | 4500 | 200 | 17.50 | 7.10 | 7.50 | 0.80 |
| Ⓜ Z510LA80A | Z510LA80A | 510 | 670 | 820(738-902) | 190 | 1355 | 100 | 6500 | 400 | 24.00 | 7.60 | 10.00 | 1.00 |
| Ⓜ Z550LA20 | 550L | 550 | 700 | 910(819-1000) | 60 | 1500 | 25 | 2500 | 95 | 14.00 | 7.60 | 7.50 | 0.80 |
| Ⓜ Z550LA40A | Z550LA40A | 550 | 700 | 910(819-1000) | 120 | 1500 | 50 | 4500 | 180 | 17.50 | 7.60 | 7.50 | 0.80 |
| Ⓜ Z550LA80A | Z550LA80A | 550 | 700 | 910(819-1000) | 220 | 1500 | 100 | 6500 | 350 | 24.00 | 8.10 | 10.00 | 1.00 |
| Ⓜ Z575LA20 | 575L | 575 | 745 | 920(819-1000) | 60 | 1500 | 25 | 2500 | 95 | 14.00 | 7.60 | 7.50 | 0.80 |
| Ⓜ Z575LA40A | Z575LA40A | 575 | 745 | 920(819-1000) | 120 | 1500 | 50 | 4500 | 180 | 17.50 | 7.60 | 7.50 | 0.80 |
| Ⓜ Z575LA80A | Z575LA80A | 575 | 745 | 920(819-1000) | 220 | 1500 | 100 | 6500 | 350 | 24.00 | 8.10 | 10.00 | 1.00 |
| Ⓜ Z600LA20 | 625L | 625 | 825 | 1000(900-1100) | 65 | 1650 | 25 | 2500 | 80 | 14.00 | 8.00 | 7.50 | 0.80 |
| Ⓜ Z600LA50A | Z600LA50A | 625 | 825 | 1000(900-1100) | 130 | 1650 | 50 | 4500 | 150 | 17.50 | 8.00 | 7.50 | 0.80 |
| Ⓜ Z600LA100A | Z600LA100A | 625 | 825 | 1000(900-1100) | 230 | 1650 | 100 | 6500 | 320 | 24.00 | 8.50 | 10.00 | 1.00 |
| Ⓜ Z660LA20 | 660L | 680 | 895 | 1100(990-1210) | 70 | 1815 | 25 | 2500 | 80 | 14.00 | 8.50 | 7.50 | 0.80 |
| Ⓜ Z660LA50A | Z660LA50A | 680 | 895 | 1100(990-1210) | 140 | 1815 | 50 | 4500 | 150 | 17.50 | 8.50 | 7.50 | 0.80 |
| Ⓜ Z660LA100A | Z660LA100A | 680 | 895 | 1100(990-1210) | 250 | 1815 | 100 | 6500 | 300 | 24.00 | 9.00 | 10.00 | 1.00 |
| Ⓜ Z1000LA80A | Z1000LA80A | 1000 | 1465 | 1800(1620-1980) | 240 | 2970 | 50 | 4500 | 100 | 17.50 | 12.00 | 15.00 | 0.80 |
| Ⓜ Z1000LA160A | Z1000LA160A | 1000 | 1465 | 1800(1620-1980) | 400 | 2970 | 100 | 6500 | 200 | 25.00 | 12.00 | 15.00 | 1.00 |

全てのリード型MOVはテープ/リール/圧着端子/トリム端子でご利用可能です。
お問い合わせ下さい。

UL規格認証のリード型MOVは、UL1414/1449及びCSA規格222101に適合しています。
CKE UL認証部品は最大電力損失:5mm-1W;7mm-0.25W;10mm-0.4W; 14mm-0.6W;20mm-1W
を#E90510に記載されております。
応答速度(標準値)は<15nsec
全製品RoHS対応