



CKE Part Number	最大許容回路電圧		バリスタ電圧	制限電圧 (Max.)		最大サージ耐量 (8/20µs)		エネルギー耐量 (JOULES)	静電容量 (標準値) (Reference)	T,mm	Y,mm
	AC <sub>RMS</sub> (V)	DC (V)	V <sub>1mA</sub> (V)	V <sub>c</sub> (V)	I <sub>p</sub> (A)	1 Time (A)	2 Times (A)	10/1000 µs	@1KHZ pf		
Z32RD Round シリーズ											
☒ Z32RD201	130	170	200(185-225)	340	200	25000	20000	210	4100	6.80	4.90
☒ Z32RD241	150	200	240(216-264)	395	200	25000	20000	240	3400	7.00	5.10
☒ Z32RD271	175	225	270(243-297)	455	200	25000	20000	255	2900	7.10	5.20
☒ Z32RD331	210	275	330(297-363)	550	200	25000	20000	300	2600	7.30	5.40
☒ Z32RD361	230	300	360(324-396)	595	200	25000	20000	315	2300	7.50	5.60
☒ Z32RD391	250	320	390(351-429)	650	200	25000	20000	330	2100	7.70	5.80
☒ Z32RD431	275	350	430(387-473)	710	200	25000	20000	360	2000	7.90	6.00
☒ Z32RD471	300	385	470(423-517)	775	200	25000	20000	380	1700	8.10	6.20
☒ Z32RD511	320	415	510(459-561)	845	200	25000	20000	430	1600	8.40	6.50
☒ Z32RD621	385	505	620(558-682)	1025	200	25000	20000	470	1300	9.00	7.10
☒ Z32RD681	420	560	680(612-748)	1120	200	25000	20000	495	1300	9.40	7.50
☒ Z32RD751	460	615	750(675-825)	1240	200	25000	20000	520	1100	9.80	7.90
☒ Z32RD781	485	640	780(702-858)	1290	200	25000	20000	550	1100	10.00	8.00
☒ Z32RD821	510	670	820(738-902)	1355	200	25000	20000	580	1000	10.20	8.30
☒ Z32RD911	550	745	910(819-1001)	1500	200	25000	20000	620	950	10.70	8.80
☒ Z32RD951	575	765	950(855-1045)	1570	200	25000	20000	650	900	11.00	9.00
☒ Z32RD102	625	825	1000(900-1100)	1650	200	25000	20000	685	840	11.20	9.30
☒ Z32RD112	680	895	1100(990-1210)	1815	200	25000	20000	750	770	11.70	9.80
☒ Z32RD122	750	970	1200(1062-1300)	2100	200	25000	20000	800	690	12.80	10.90
☒ Z32RD142	880	1150	1400(1245-1520)	2290	200	25000	20000	850	590	13.80	11.90
☒ Z32RD162	1000	1200	1600(1414-1728)	2700	200	25000	20000	900	520	14.90	13.00
Z34SQ Square シリーズ											
☒ Z34SQ201	130	170	200(185-225)	340	300	40000	25000	310	7900	6.80	4.90
☒ Z34SQ221	140	180	220(198-242)	360	300	40000	25000	330	7200	6.90	5.00
☒ Z34SQ241	150	200	240(216-264)	395	300	40000	25000	360	6600	7.00	5.10
☒ Z34SQ271	175	225	270(243-297)	455	300	40000	25000	390	5600	7.10	5.20
☒ Z34SQ331	210	275	330(297-363)	550	300	40000	25000	460	5000	7.30	5.40
☒ Z34SQ361	230	300	360(324-396)	595	300	40000	25000	475	4400	7.50	5.60
☒ Z34SQ391	250	320	390(351-429)	650	300	40000	25000	490	4100	7.70	5.80
☒ Z34SQ431	275	350	430(387-473)	710	300	40000	25000	550	3800	7.90	6.00
☒ Z34SQ471	300	385	470(423-517)	775	300	40000	25000	600	3400	8.10	6.20
☒ Z34SQ511	320	415	510(459-561)	845	300	40000	25000	640	3200	8.40	6.50
☒ Z34SQ561	350	460	560(504-616)	920	300	40000	25000	710	2900	8.50	6.80
☒ Z34SQ621	385	505	620(558-682)	1025	300	40000	25000	720	2600	9.00	7.10
☒ Z34SQ681	420	560	680(612-748)	1120	300	40000	25000	750	2400	9.40	7.50
☒ Z34SQ751	460	615	750(675-825)	1240	300	40000	25000	780	2200	9.80	7.90
☒ Z34SQ781	485	640	780(702-858)	1290	300	40000	25000	820	2100	10.00	8.00
☒ Z34SQ821	510	670	820(738-902)	1355	300	40000	25000	900	2000	10.20	8.30
☒ Z34SQ911	550	745	910(819-1001)	1500	300	40000	25000	960	1800	10.70	8.80
☒ Z34SQ951	575	765	950(855-1045)	1570	300	40000	25000	1000	1700	11.00	9.00
☒ Z34SQ102	625	825	1000(900-1100)	1650	300	40000	25000	1055	1600	11.20	9.30
☒ Z34SQ112	680	895	1100(990-1210)	1815	300	40000	25000	1155	1500	11.70	9.80
☒ Z34SQ122	750	970	1200(1062-1300)	2100	300	40000	25000	1200	1300	12.80	10.90
☒ Z34SQ142	880	1150	1400(1245-1520)	2290	300	40000	25000	1300	1100	13.80	11.90
☒ Z34SQ162	1000	1200	1600(1414-1728)	2700	300	40000	25000	1400	1000	14.90	13.00

最大電力損失: Z32RD-1.2W Z34SQ-1.4W

UL規格認証のリード型MOVは、UL1414/1449及びCSAクラス222101に適合しています。

CKE UL認証部品は#E90510に記載されております。

応答速度(標準値)は<15nsec

全製品RoHS対応