

FEATURES:



- I/O Isolation of 4,000VAC
- Efficiency up to 87%
- Input under voltage lock out
- IGBT dedicated DC-DC converter
- Operating temperature range: -40 to +85°C
- Industrial Standard Pin-out

Models
Dual output



| Model | Input Voltage (V) | Input current FL (mA) | Output Voltage (V) | Max Output Current (mA) | Max Capacitive Load (uF) | Efficiency (%) |
|---------------------|-------------------|-----------------------|--------------------|-------------------------|--------------------------|----------------|
| AM5NG-151509DH40-NZ | 13.5-16.5 | 368 | +15 / -9 | ±200 | 1000 | 87 |

NOTE: All specifications in this datasheet are measured at an ambient temperature of 25°C, humidity<75%, nominal input voltage and at rated output load unless otherwise specified.

Input Specifications

| Parameters | Nominal | Typical | Maximum | Units |
|--------------------------------|-----------|-----------|---------|-------|
| Voltage range | 15V Input | 13.5-16.5 | | VDC |
| Filter | Capacitor | | | |
| No Load Input Current | 15V Input | | 20 | mA |
| Input Under Voltage Protection | | 12 | | VDC |

Isolation Specifications

| Parameters | Conditions | Typical | Rated | Units |
|--------------------|-------------|---------|-------|-------|
| Tested I/O voltage | 60sec, <1mA | | 4000 | VAC |
| Resistance | | >1000 | | MOhm |
| Capacitance | 1MHz/0.1V | 3 | | pF |

Output Specifications

| Parameters | Conditions | Typical | Maximum | Units |
|--------------------------|--|---------|-----------|----------|
| Voltage accuracy | See Tolerance Graph | | | % |
| Output Current | +Io Vin = 15VDC | 200 | 250 | mA |
| | -Io Vin = 15VDC | -200 | -250 | |
| Output Voltage | +Vo Vin=15VDC, Pin16 & Pin14 +Io=+200mA | 15 | 13.5~16.5 | VDC |
| | -Vo Vin=15VDC, Pin11 & Pin9 -Io=-200mA | -9 | -8.1~-9.9 | |
| Short Circuit protection | Continuous, auto restart | | | |
| Line voltage regulation | Full load | ±1.2 | ±1.5 | % of Vin |
| Load voltage regulation | 10 – 100% load | ±8 | ±10 | % |
| Temperature coefficient | Full load | | ±0.03 | %/°C |
| Ripple & Noise | 20MHz Bandwidth | 80 | 120 | mV p-p |

General Specifications

| Parameters | Conditions | Typical | Maximum | Units |
|------------------------|---|--------------------------|---------|-------|
| Switching frequency | 100% load | 280 | | kHz |
| Operating temperature | Without derating | -40 to +85 | | °C |
| Storage temperature | | -55 to +125 | | °C |
| Case temperature Rise | Ta = 25 °C | | 30 | °C |
| Cooling | Free air convection | | | |
| Humidity | | | 95 | % RH |
| Case material | Non-conductive black plastic (UL94V-0 rated) | | | |
| Weight | | 11.4 | | g |
| Dimensions (L x W x H) | 1.244 x 0.799 x 0.402 inches | 31.60 x 20.30 x 10.20 mm | | |
| MTBF | >1,000,000hrs (MIL-HDBK -217F, Ground Benign, t=+25 °C) | | | |

Safety Specifications


Parameters

Standards Electrostatic Discharge Immunity IEC 61000-4-2, Contact +/-4kV, Criteria B

Pin Out Specifications


| Pin | Single |
|-----|------------|
| 2 | -Vin |
| 3 | -Vin |
| 9 | Common |
| 11 | - V Output |
| 14 | + V Output |
| 16 | Common |
| 22 | +Vin |
| 23 | +Vin |

Dimensions




All dimensions are typical: millimeters (inches)
Pin Diameter: 0.50 ± 0.05 (0.02 ± 0.002)
Pin Pitch Tolerance: ± 0.35 (± 0.014)
Case Tolerance: ± 0.5 (± 0.02)

Tolerance Graph



Application Circuit



| | Specification |
|-------|---------------|
| C1 | 100uF/63V EC |
| C2,C3 | 100uF/35V EC |
| C4,C5 | 10uF/25V CC |

NOTE: **1.** Datasheets are updated as needed and as such, specifications are subject to change without notice. Once printed or downloaded, datasheets are no longer controlled by Aimtec; refer to www.aimtec.com for the most current product specifications. **2.** Product labels shown, including safety agency certifications on labels, may vary based on the date manufactured. **3.** Mechanical drawings and specifications are for reference only. **4.** All specifications are measured at an ambient temperature of 25°C, humidity<75%, nominal input voltage and at rated output load unless otherwise specified. **5.** Aimtec may not have conducted destructive testing or chemical analysis on all internal components and chemicals at the time of publishing this document. CAS numbers and other limited information are considered proprietary and may not be available for release. **6.** This product is not designed for use in critical life support systems, equipment used in hazardous environments, nuclear control systems or other such applications which necessitate specific safety and regulatory standards other the ones listed in this datasheet. **7.** Warranty is in accordance with Aimtec's standard Terms of Sale available at www.aimtec.com.